


Masonry Drills

BOOSTER — Spline Drive Shank

| EUROPE | CHROME VANADIUM STEEL | HRVCB* POINT |
|--|--|--|
| PERFORMANCE LEVEL PLASTER XXXX SOFT STONE..... XXXX HARD STONE XXXX REINFORCED CONCRETE XXX VIBRATED CONCRETE XXXX SUPER CONCRETE XXXX GRANITE XXX MARBLE XXX BRICK..... XXXX TILE CERAMICS..... GLASS..... |  | CHARACTERISTICS TREATED MILLED BODY "BOOSTER" HEAD 3 CARBIDE TIPS WITH 6 CUTTINGS EDGES COMFORTABLE TO USE HIGH TEMPERATURE BRAZING SANDBLASTED FINISH |



SDS BOOSTER MAX HEAD — The head has six cutting edges which make it highly efficient. The six cutting edges perfectly guide the drill bit which makes the drilling effort more progressive and increases the penetration speed. The BOOSTER MAX head reduces vibration therefor increases the comfort of drilling.

Packaging: All sizes are individually packaged.

SERIES 1830

| SIZE | FLUTE LENGTH | OVERALL LENGTH | EDP NUMBER | LIST PRICE |
|-------|--------------|----------------|------------|------------|
| 5/8 | 6" | 11" | 183F14011 | \$109.22 |
| 5/8 | 11" | 16" | 183F14016 | 123.01 |
| 5/8 | 18" | 23" | 183F14023 | 143.78 |
| 5/8 | 22" | 27" | 183F14027 | 196.97 |
| 5/8 | 31" | 36" | 183F14036 | 220.54 |
| 3/4 | 7" | 12" | 183F14812 | 119.21 |
| 3/4 | 11" | 16" | 183F14816 | 125.84 |
| 3/4 | 18" | 23" | 183F14823 | 151.55 |
| 3/4 | 31" | 36" | 183F14836 | 228.78 |
| 7/8 | 11" | 16" | 183F15616 | 136.72 |
| 7/8 | 18" | 23" | 183F15623 | 156.87 |
| 1" | 11" | 16" | 183F16416 | 139.45 |
| 1" | 18" | 21" | 183F16421 | 161.26 |
| 1" | 31" | 36" | 183F16436 | 276.95 |
| 1-1/8 | 11" | 16" | 183F20816 | 181.70 |
| 1-1/8 | 18" | 21" | 183F20821 | 196.30 |
| 1-1/4 | 11" | 16" | 183F21616 | 202.82 |
| 1-1/4 | 18" | 23" | 183F21623 | 220.51 |
| 1-1/4 | 31" | 36" | 183F21636 | 354.59 |
| 1-3/8 | 18" | 21" | 183F22421 | 239.30 |
| 1-1/2 | 18" | 23" | 183F23223 | 296.05 |

*High Resistance Vacuum Copper Brazed