

Hand Taps

MACHINE SCREW SIZES

HIGH SPEED M-2 STEEL

GROUND THREAD



"Hand Taps" are the most popular style in general machine tapping operations and are appropriate for the vast majority of materials and conditions. They are for general use in production tapping or hand operations. Taper, Plug and Bottoming styles provide great versatility in tough materials, blind and thru holes. Taper Style - Starts the thread square with the workpiece. Plug Style - Generally used in thru holes. Bottoming Style - Generates the thread to the bottom.

Packaging: #0 thru #12, 12 per box.

IMPORT			SERIES 2000E				TAPER, PLUG & BOTTOM			LIST PRICE EACH	EDP NUMBER SETS	LIST PRICE SETS
TAP SIZES	NC	NF	PITCH DIA LIMITS	NO OF FLUTES	LENGTH OF THREAD	OVER-ALL LENGTH	TAPER	PLUG	BOTT			
0	--	80	H1	2	5/16	1-5/8	20E000FT	20E000FP	20E000FB	\$13.05	20E000FS	\$39.15
1	64	--	H1	2	3/8	1-11/16	20E001CT	20E001CP	20E001CB	12.75	20E001CS	38.25
1	--	72	H1	2	3/8	1-11/16	20E001FT	20E001FP	20E001FB	12.75	20E001FS	38.25
2	56	--	H2	3	7/16	1-3/4	20E002CT	20E002CP	20E002CB	10.44	20E002CS	31.32
2	--	64	H2	3	7/16	1-3/4	20E002FT	20E002FP	20E002FB	10.44	20E002FS	31.32
3	48	--	H2	3	1/2	1-13/16	20E003CT	20E003CP	20E003CB	8.31	20E003CS	24.93
3	--	56	H2	3	1/2	1-13/16	20E003FT	20E003FP	20E003FB	8.31	20E003FS	24.93
4	40	--	H2	3	9/16	1-7/8	20E004CT	20E004CP	20E004CB	5.87	20E004CS	17.61
4	--	48	H2	3	9/16	1-7/8	20E004FT	20E004FP	20E004FB	6.53	20E004FS	19.59
4	--	36	H2	3	9/16	1-7/8	20E004ST	20E004SP	20E004SB	6.53	20E004SS	19.59
5	40	--	H2	3	5/8	1-15/16	20E005CT	20E005CP	20E005CB	6.09	20E005CS	18.27
5	--	44	H2	3	5/8	1-15/16	20E005FT	20E005FP	20E005FB	6.53	20E005FS	19.59
6	32	--	H3	3	11/16	2"	20E006CT	20E006CP	20E006CB	4.57	20E006CS	13.71
6	--	40	H2	3	11/16	2"	20E006FT	20E006FP	20E006FB	4.79	20E006FS	14.37
8	32	--	H3	4	3/4	2-1/8	20E008CT	20E008CP	20E008CB	4.79	20E008CS	14.37
8	--	36	H2	4	3/4	2-1/8	20E008FT	20E008FP	20E008FB	4.79	20E008FS	14.37
10	24	--	H3	4	7/8	2-3/8	20E010CT	20E010CP	20E010CB	4.79	20E010CS	14.37
10	--	32	H3	4	7/8	2-3/8	20E010FT	20E010FP	20E010FB	4.79	20E010FS	14.37
12	24	--	H3	4	15/16	2-3/8	20E012CT	20E012CP	20E012CB	5.22	20E012CS	15.66
12	--	28	H3	4	15/16	2-3/8	20E012FT	20E012FP	20E012FB	5.22	20E012FS	15.66