


# Hand Taps

**FRACTIONAL SIZES**

**HIGH SPEED M-2 STEEL**

**GROUND THREAD**



"Hand Taps" are the most popular style in general machine tapping operations and are appropriate for the vast majority of materials and conditions. They are for general use in production tapping or hand operations. Taper, Plug and Bottoming styles provide great versatility in tough materials, blind and thru holes. Taper Style - Starts the thread square with the workpiece. Plug Style-Generally used in thru holes. Bottoming Style-Generates the thread to the bottom.

Packaging: 0 thru 1/4", 12 per box. 5/16" thru 1/2", 6 per box. 9/16" thru 1", 3 per box. 1-1/8" & up individually packaged.

**IMPORT**

**SERIES 200E**

**TAPER, PLUG & BOTTOM**

TAP SIZES	NC	NF	PITCH DIA LIMITS	NO OF FLUTES	LENGTH OF THREAD	OVER ALL LENGTH	EDP NUMBERS			LIST PRICE EACH	EDP NUMBER SETS	LIST PRICE SETS
							TAPER	PLUG	BOTT			
1/4	20	-	H3	4	1"	2-1/2	20E116CT	20E116CP	20E116CB	\$5.00	20E116CS	\$15.00
1/4	-	28	H3	4	1"	2-1/2	20E116FT	20E116FP	20E116FB	5.00	20E116FS	15.00
5/16	18	-	H3	4	1-1/8	2-23/32	20E120CT	20E120CP	20E120CB	6.31	20E120CS	18.93
5/16	-	24	H3	4	1-1/8	2-23/32	20E120FT	20E120FP	20E120FB	6.31	20E120FS	18.93
3/8	16	-	H3	4	1-1/4	2-15/16	20E124CT	20E124CP	20E124CB	7.18	20E124CS	21.54
3/8	-	24	H3	4	1-1/4	2-15/16	20E124FT	20E124FP	20E124FB	7.18	20E124FS	21.54
7/16	14	-	H3	4	1-7/16	3-5/32	20E128CT	20E128CP	20E128CB	11.75	20E128CS	35.25
7/16	-	20	H3	4	1-1/16	3-5/32	20E128FT	20E128FP	20E128FB	11.75	20E128FS	35.25
1/2	13	-	H3	4	1-21/32	3-3/8	20E132CT	20E132CP	20E132CB	13.05	20E132CS	39.15
1/2	-	20	H3	4	1-21/32	3-3/8	20E132FT	20E132FP	20E132FB	13.05	20E132FS	39.15
9/16	12	-	H3	4	1-21/32	3-19/32	20E136CT	20E136CP	20E136CB	20.88	20E136CS	62.64
9/16	-	18	H3	4	1-21/32	3-19/32	20E136FT	20E136FP	20E136FB	20.88	20E136FS	62.64
5/8	11	-	H3	4	1-13/16	3-13/16	20E140CT	20E140CP	20E140CB	26.10	20E140CS	78.30
5/8	-	18	H3	4	1-13/16	3-13/16	20E140FT	20E140FP	20E140FB	26.10	20E140FS	78.30
11/16	11	-	H3	4	1-13/16	4-1/32	20E144CT	20E144CP	20E144CB	31.10	20E144CS	93.30
11/16	-	16	H3	4	1-13/16	4-1/32	20E144FT	20E144FP	20E144FB	31.10	20E144FS	93.30
3/4	10	-	H3	4	2"	4-1/4	20E148CT	20E148CP	20E148CB	34.80	20E148CS	104.40
3/4	-	16	H3	4	2"	4-1/4	20E148FT	20E148FP	20E148FB	34.80	20E148FS	104.40
7/8	9	-	H4	4	2-7/32	4-11/16	20E156CT	20E156CP	20E156CB	48.50	20E156CS	145.50
7/8	-	14	H4	4	2-7/32	4-11/16	20E156FT	20E156FP	20E156FB	48.50	20E156FS	145.50
1"	8	-	H4	4	2-1/2	5-1/8	20E164CT	20E164CP	20E164CB	65.25	20E164CS	195.75
1"	-	12	H4	4	2-1/2	5-1/8	20E164FT	20E164FP	20E164FB	66.34	20E164FS	199.02
1"	-	14	H4	4	2-1/2	5-1/8	20E164ST	20E164SP	20E164SB	66.34	20E164SS	199.02
1-1/8	7	-	H4	4	2-9/16	5-7/16	20E208CT	20E208CP	20E208CB	103.23	20E208CS	309.69
1-1/8	-	12	H4	4	2-9/16	5-7/16	20E208FT	20E208FP	20E208FB	109.62	20E208FS	328.86
1-1/4	7	-	H4	4	2-9/16	5-3/4	20E216CT	20E216CP	20E216CB	135.20	20E216CS	405.60
1-1/4	-	12	H4	6	2-9/16	5-3/4	20E216FT	20E216FP	20E216FB	137.94	20E216FS	413.82
1-3/8	6	-	H4	4	3"	6-1/16	20E224CT	20E224CP	20E224CB	170.82	20E224CS	512.46
1-3/8	-	12	H4	6	3"	6-1/16	20E224FT	20E224FP	20E224FB	171.84	20E224FS	515.52
1-1/2	6	-	H4	4	3"	6-3/8	20E232CT	20E232CP	20E232CB	196.40	20E232CS	589.20
1-1/2	-	12	H4	6	3"	6-3/8	20E232FT	20E232FP	20E232FB	200.06	20E232FS	600.18