

# Nitro Hand Taps

**MACHINE SCREW SIZES HIGH SPEED M-7N STEEL GROUND THREAD**



See page 01 for Technical information on *Nitro* Taps.

Taper Style - Starts the thread square with the workpiece. Plug Style-Generally used in thru holes. Bottoming Style-Generates the thread to the bottom.

Packaging: #0 thru #12, 12 per box.

MADE IN USA			SERIES 2000N				TAPER, PLUG & BOTTOM					
TAP SIZES	NC	NF	PITCH DIA LIMITS	NO OF FLUTES	LENGTH OF THREAD	OVER ALL LENGTH	EDP NUMBERS			LIST PRICE EACH	EDP NUMBER SETS	LIST PRICE SETS
							TAPER	PLUG	BOTT			
0	--	80	H1	2	5/16	1-5/8	20N000FT	20N000FP	20N000FB	\$20.01	20N000FS	\$60.03
1	64	--	H1	2	3/8	1-11/16	20N001CT	20N001CP	20N001CB	18.88	20N001CS	56.64
1	--	72	H1	2	3/8	1-11/16	20N001FT	20N001FP	20N001FB	18.88	20N001FS	56.64
2	56	--	H2	3	7/16	1-3/4	20N002CT	20N002CP	20N002CB	18.92	20N002CS	56.76
2	--	64	H2	3	7/16	1-3/4	20N002FT	20N002FP	20N002FB	18.92	20N002FS	56.76
3	48	--	H2	3	1/2	1-13/16	20N003CT	20N003CP	20N003CB	13.22	20N003CS	39.66
3	--	56	H2	3	1/2	1-13/16	20N003FT	20N003FP	20N003FB	13.22	20N003FS	39.66
4	40	--	H2	3	9/16	1-7/8	20N004CT	20N004CP	20N004CB	13.22	20N004CS	39.66
4	--	48	H2	3	9/16	1-7/8	20N004FT	20N004FP	20N004FB	13.22	20N004FS	39.66
4	--	36	H2	3	9/16	1-7/8	20N004ST	20N004SP	20N004SB	13.22	20N004SS	39.66
5	40	--	H2	3	5/8	1-15/16	20N005CT	20N005CP	20N005CB	9.87	20N005CS	29.61
5	--	44	H2	3	5/8	1-15/16	20N005FT	20N005FP	20N005FB	9.87	20N005FS	29.61
6	32	--	H3	3	11/16	2"	20N006CT	20N006CP	20N006CB	9.31	20N006CS	27.93
6	--	40	H2	3	11/16	2"	20N006FT	20N006FP	20N006FB	9.31	20N006FS	27.93
8	32	--	H3	4	3/4	2-1/8	20N008CT	20N008CP	20N008CB	9.31	20N008CS	27.93
8	--	36	H2	4	3/4	2-1/8	20N008FT	20N008FP	20N008FB	9.31	20N008FS	27.93
10	24	--	H3	4	7/8	2-3/8	20N010CT	20N010CP	20N010CB	9.31	20N010CS	27.93
10	--	32	H3	4	7/8	2-3/8	20N010FT	20N010FP	20N010FB	9.31	20N010FS	27.93
12	24	--	H3	4	15/16	2-3/8	20N012CT	20N012CP	20N012CB	9.96	20N012CS	29.88
12	--	28	H3	4	15/16	2-3/8	20N012FT	20N012FP	20N012FB	9.96	20N012FS	29.88