

"Left Hand" Taps

MACHINE & FRAC SIZES

HIGH SPEED M-7 STEEL

GROUND THREAD



"Hand Taps" are the most popular style in general machine tapping operations and are appropriate for the vast majority of materials and conditions. They are for general use in production tapping or hand operations. Taper, Plug and Bottoming styles provide great versatility in tough materials, blind and thru holes. Taper Style - Starts the thread square with the workpiece. Plug Style-Generally used in thru holes. Bottoming Style-Generates the thread to the bottom.

Packaging: 6 thru 1/4", 12 per box. 5/16" thru 1/2", 6 per box. 9/16" thru 1", 3 per box. 1-1/8" & up individually packaged.

MADE IN USA

SERIES 2300

TAPER, PLUG & BOTTOM

TAP SIZES	NC	NF	PITCH DIAMETER LIMITS	NUMBER OF FLUTES	OVERALL LENGTH	EDP NUMBERS			LIST PRICE EACH
						TAPER	PLUG	BOTTOM	
6	32	--	H3	4	2"	23A006CT	23A006CP	23A006CB	\$13.38
8	32	--	H3	4	2-1/8	23A008CT	23A008CP	23A008CB	14.49
10	24	--	H3	4	2-3/8	23A010CT	23A010CP	23A010CB	14.49
10	--	32	H3	4	2-3/8	23A010FT	23A010FP	23A010FB	14.49
1/4	20	--	H3	4	2-1/2	23A116CT	23A116CP	23A116CB	13.70
1/4	--	28	H3	4	2-1/2	23A116FT	23A116FP	23A116FB	13.70
5/16	18	--	H3	4	2-23/32	23A120CT	23A120CP	23A120CB	15.31
5/16	--	24	H3	4	2-23/32	23A120FT	23A120FP	23A120FB	15.31
3/8	16	--	H3	4	2-5/16	23A124CT	23A124CP	23A124CB	19.84
3/8	--	24	H3	4	2-5/16	23A124FT	23A124FP	23A124FB	19.84
7/16	14	--	H3	4	3-5/32	23A128CT	23A128CP	23A128CB	28.84
7/16	--	20	H3	4	3-5/32	23A128FT	23A128FP	23A128FB	28.84
1/2	13	--	H3	4	3-3/8	23A132CT	23A132CP	23A132CB	33.67
1/2	--	20	H3	4	3-3/8	23A132FT	23A132FP	23A132FB	33.67
9/16	12	--	H3	4	3-19/32	23A136CT	23A136CP	23A136CB	50.20
9/16	--	18	H3	4	3-19/32	23A136FT	23A136FP	23A136FB	50.20
5/8	11	--	H3	4	3-3/16	23A140CT	23A140CP	23A140CB	63.51
5/8	--	18	H3	4	3-3/16	23A140FT	23A140FP	23A140FB	63.51
3/4	10	--	H3	4	4-1/4	23A148CT	23A148CP	23A148CB	83.48
3/4	--	16	H3	4	4-1/4	23A148FT	23A148FP	23A148FB	83.48
7/8	9	--	H4	4	4-11/16	23A156CT	23A156CP	23A156CB	115.23
7/8	--	14	H4	4	4-11/16	23A156FT	23A156FP	23A156FB	115.23
1"	8	--	H4	4	5-1/8	23A164CT	23A164CP	23A164CB	125.74
1"	--	12	H4	4	5-1/8	23A164FT	23A164FP	23A164FB	125.74
1"	--	14	H4	4	5-1/8	23A164ST	23A164SP	23A164SB	125.74
1-1/8	7	--	H4	4	5-7/16	23A208CT	23A208CP	23A208CB	317.05
1-1/8	--	12	H4	4	5-7/16	23A208FT	23A208FP	23A280FB	317.05
1-1/4	7	--	H4	4	5-3/4	23A216CT	23A216CP	23A216CB	400.24
1-1/4	--	12	H4	6	5-3/4	23A216FT	23A216FP	23A216FB	400.24
1-3/8	6	--	H4	4	6"	23A224CT	23A224CP	23A224CB	498.51
1-3/8	--	12	H4	6	6"	23A224FT	23A224FP	23A224FB	498.51
1-1/2	6	--	H4	4	6-1/4	23A232CT	23A232CP	23A232CB	580.53
1-1/2	--	12	H4	6	6-1/4	23A232FT	23A232FP	23A232FB	580.53

Please specify Taper, Plug or Bottoming