


"Left Hand" Taps

MACHINE & FRAC SIZES

HIGH SPEED M-2 STEEL

GROUND THREAD



"Hand Taps" are the most popular style in general machine tapping operations and are appropriate for the vast majority of materials and conditions. They are for general use in production tapping or hand operations. Taper, Plug and Bottoming styles provide great versatility in tough materials, blind and thru holes. Taper Style - Starts the thread square with the workpiece. Plug Style-Generally used in thru holes. Bottoming Style-Generates the thread to the bottom.

Packaging: 0 thru 1/4", 12 per box. 5/16" thru 1/2", 6 per box. 9/16" thru 1", 3 per box. 1-1/8" & up individually packaged.

IMPORT

SERIES 2300E

TAPER, PLUG & BOTTOM

TAP SIZES	NC	NF	PITCH DIAMETER LIMITS	NUMBER OF FLUTES	OVERALL LENGTH	EDP NUMBERS			LIST PRICE EACH
						TAPER	PLUG	BOTTOM	
1/4	20	--	H3	4	2-1/2	23E116CT	23E116CP	23E116CB	\$9.48
1/4	--	28	H3	4	2-1/2	23E116FT	23E116FP	23E116FB	9.48
5/16	18	--	H3	4	2-23/32	23E120CT	23E120CP	23E120CB	10.57
5/16	--	24	H3	4	2-23/32	23E120FT	23E120FP	23E120FB	10.57
3/8	16	--	H3	4	2-5/16	23E124CT	23E124CP	23E124CB	13.70
3/8	--	24	H3	4	2-5/16	23E124FT	23E124FP	23E124FB	13.70
7/16	14	--	H3	4	3-5/32	23E128CT	23E128CP	23E128CB	19.92
7/16	--	20	H3	4	3-5/32	23E128FT	23E128FP	23E128FB	19.92
1/2	13	--	H3	4	3-3/8	23E132CT	23E132CP	23E132CB	23.23
1/2	--	20	H3	4	3-3/8	23E132FT	23E132FP	23E132FB	23.23
9/16	12	--	H3	4	3-19/32	23E136CT	23E136CP	23E136CB	28.32
9/16	--	18	H3	4	3-19/32	23E136FT	23E136FP	23E136FB	28.32
5/8	11	--	H3	4	3-3/16	23E140CT	23E140CP	23E140CB	34.32
5/8	--	18	H3	4	3-3/16	23E140FT	23E140FP	23E140FB	34.32
3/4	10	--	H3	4	4-1/4	23E148CT	23E148CP	23E148CB	46.15
3/4	--	16	H3	4	4-1/4	23E148FT	23E148FP	23E148FB	46.15
7/8	9	--	H4	4	4-11/16	23E156CT	23E156CP	23E156CB	61.68
7/8	--	14	H4	4	4-11/16	23E156FT	23E156FP	23E156FB	61.68
1"	8	--	H4	4	5-1/8	23E164CT	23E164CP	23E164CB	83.04
1"	--	12	H4	4	5-1/8	23E164FT	23E164FP	23E164FB	83.04
1"	--	14	H4	4	5-1/8	23E164ST	23E164SP	23E164SB	83.04
1-1/8	7	--	H4	4	5-7/16	23E208CT	23E208CP	23E208CB	101.96
1-1/8	--	12	H4	4	5-7/16	23E208FT	23E208FP	23E280FB	101.96
1-1/4	7	--	H4	4	5-3/4	23E216CT	23E216CP	23E216CB	130.37
1-1/4	--	12	H4	6	5-3/4	23E216FT	23E216FP	23E216FB	130.37
1-3/8	6	--	H4	4	6"	23E224CT	23E224CP	23E224CB	162.55
1-3/8	--	12	H4	6	6"	23E224FT	23E224FP	23E224FB	162.55
1-1/2	6	--	H4	4	6-1/4	23E232CT	23E232CP	23E232CB	200.60
1-1/2	--	12	H4	6	6-1/4	23E232FT	23E232FP	23E232FB	200.60
1-3/4	8	--	H4	6	7"	23E248NT	23E248NP	23E248NB	246.65

Please specify Taper, Plug or Bottoming