

Carbon Hand Taps

MACHINE & FRAC SIZES

HIGH CARBON STEEL

CUT THREAD



Carbon Steel Hand Taps are used to rethread damaged or jammed threads or thread mild steels. Taper, Plug and Bottoming styles provide great versatility in tough materials, blind and thru holes. Taper Style - Starts the thread square with the workpiece. Plug Style - Generally used in thru holes. Bottoming Style - Generates the thread to the bottom.

Packaging: 0 thru 1/4", 12 per box. 5/16" thru 1/2", 6 per box. 9/16" thru 1", 3 per box. 1-1/8" & up individually packaged.

IMPORT

SERIES 200C

TAPER, PLUG & BOTTOM

TAP SIZES	NC	NF	PITCH DIA LIMITS	NUMBER OF FLUTES	LENGTH OF THREAD	OVERALL LENGTH	EDP NUMBERS			LIST PRICE EACH
							TAPER	PLUG	BOTT	
0	--	80	H1	2	5/16	1-5/8	20C000FT	20C000FP	20C000FB	\$5.74
1	64	--	H1	2	3/8	1-11/16	20C001CT	20C001CP	20C001CB	5.39
1	--	72	H1	2	3/8	1-11/16	20C001FT	20C001FP	20C001FB	5.39
2	56	--	H2	3	7/16	1-3/4	20C002CT	20C002CP	20C002CB	5.09
2	--	64	H2	3	7/16	1-3/4	20C002FT	20C002FP	20C002FB	5.09
3	48	--	H2	3	1/2	1-13/16	20C003CT	20C003CP	20C003CB	3.70
3	--	56	H2	3	1/2	1-13/16	20C003FT	20C003FP	20C003FB	3.70
4	40	--	H2	3	9/16	1-7/8	20C004CT	20C004CP	20C004CB	3.70
4	--	48	H2	3	9/16	1-7/8	20C004FT	20C004FP	20C004FB	3.70
4	--	36	H2	3	9/16	1-7/8	20C004AT	20C004AP	20C004AB	3.70
5	40	--	H2	3	5/8	1-15/16	20C005CT	20C005CP	20C005CB	3.09
5	--	44	H2	3	5/8	1-15/16	20C005FT	20C005FP	20C005FB	3.09
6	32	--	H3	3	11/16	2"	20C006CT	20C006CP	20C006CB	3.09
6	--	40	H2	3	11/16	2"	20C006FT	20C006FP	20C006FB	3.09
8	32	--	H3	4	3/4	2-1/8	20C008CT	20C008CP	20C008CB	3.09
8	--	36	H2	4	3/4	2-1/8	20C008FT	20C008FP	20C008FB	3.09
10	24	--	H3	4	7/8	2-3/8	20C010CT	20C010CP	20C010CB	3.39
10	--	32	H3	4	7/8	2-3/8	20C010FT	20C010FP	20C010FB	3.39
12	24	--	H3	4	15/16	2-3/8	20C012CT	20C012CP	20C012CB	3.87
12	--	28	H3	4	15/16	2-3/8	20C012FT	20C012FP	20C012FB	3.87
1/4	20	--	H3	4	1"	2-1/2	20C116CT	20C116CP	20C116CB	3.09
1/4	--	28	H3	4	1"	2-1/2	20C116FT	20C116FP	20C116FB	3.09
5/16	18	--	H3	4	1-1/8	2-23/32	20C120CT	20C120CP	20C120CB	3.78
5/16	--	24	H3	4	1-1/8	2-23/32	20C120FT	20C120FP	20C120FB	3.78
3/8	16	--	H3	4	1-1/4	2-15/16	20C124CT	20C124CP	20C124CB	4.22
3/8	--	24	H3	4	1-1/4	2-15/16	20C124FT	20C124FP	20C124FB	4.22
7/16	14	--	H3	4	1-7/16	3-5/32	20C128CT	20C128CP	20C128CB	5.57
7/16	--	20	H3	4	1-7/16	3-5/32	20C128FT	20C128FP	20C128FB	5.57
1/2	13	--	H3	4	1-21/32	3-3/8	20C132CT	20C132CP	20C132CB	6.35
1/2	--	20	H3	4	1-21/32	3-3/8	20C132FT	20C132FP	20C132FB	6.35
9/16	12	--	H3	4	1-21/32	3-19/32	20C136CT	20C136CP	20C136CB	8.66
9/16	--	18	H3	4	1-21/32	3-19/32	20C136FT	20C136FP	20C136FB	8.66
5/8	11	--	H3	4	1-13/16	3-13/16	20C140CT	20C140CP	20C140CB	9.57
5/8	--	18	H3	4	1-13/16	3-13/16	20C140FT	20C140FP	20C140FB	9.57
3/4	10	--	H3	4	2"	4-1/4	20C148CT	20C148CP	20C148CB	13.66
3/4	--	16	H3	4	2"	4-1/4	20C148FT	20C148FP	20C148FB	13.66
7/8	9	--	H4	4	2-7/32	4-11/16	20C156CT	20C156CP	20C156CB	19.14
7/8	--	14	H4	4	2-7/32	4-11/16	20C156FT	20C156FP	20C156FB	19.14
1"	8	--	H4	4	2-1/2	5-1/8	20C164CT	20C164CP	20C164CB	23.79
1"	--	12	H4	4	2-1/2	5-1/8	20C164FT	20C164FP	20C164FB	23.79
1-1/8	7	--	H4	4	2-9/16	5-7/16	20C208CT	20C208CP	20C208CB	47.55
1-1/8	--	12	H4	4	2-9/16	5-7/16	20C208FT	20C208FP	20C208FB	47.55
1-1/4	7	--	H4	4	2-9/16	5-3/4	20C216CT	20C216CP	20C216CB	54.72
1-1/4	--	12	H4	6	2-9/16	5-3/4	20C216FT	20C216FP	20C216FB	54.72
1-3/8	6	--	H4	4	3"	6-1/16	20C224CT	20C224CP	20C224CB	63.03
1-3/8	--	12	H4	6	3"	6-1/16	20C224FT	20C224FP	20C224FB	63.03
1-1/2	6	--	H4	4	3"	6-3/8	20C232CT	20C232CP	20C232CB	74.30
1-1/2	--	12	H4	6	3"	6-3/8	20C232FT	20C232FP	20C232FB	74.30